



Allen-Bradley

Product Profile

VersaView™ 200R Non-Display Industrial Computer

Bulletin 6155R

The Allen-Bradley VersaView 200R non-display computer provides the functionality needed to run small visual interface and maintenance applications. Combining the 200R computer with an Allen-Bradley VersaView industrial monitor creates a compact way to view drawings, modify ladder logic, and review manuals.

The VersaView 200R computer is available in standard and performance models. The standard model provides the computing power necessary for client side visual interface and maintenance applications. However, if a standalone application is needed, use a performance model.

Advantages

Like all VersaView products, the VersaView 200R computer includes the following tools and services to provide reliable computing power on the factory floor:

- Application interoperability
- Technology change management
- Rugged yet cost-effective platforms for today's demanding factory environments
- Factory system recovery CD
- Unit level immediate exchange program
- Complete package for immediate startup
- Global sales and support
- Quick delivery



System Components	
A	Audio Port
B	Parallel Port
C	Serial Port
D	10/100M Ethernet Port
E	2 USB Ports
F	Keyboard/Mouse Port (PS/2)
G	VGA Port
H	PCMCIA (Performance)



VersaView 200R Selection Table

Catalog Number	Standard: 800 MHz Via C3 256 MB RAM 40 GB Hard Drive	Performance: 1 GHz Via C3 512 MB RAM 40 GB Hard Drive PCMCIA Slot (Type I, II, III)	Windows XP
6155R-NSXPH	X		X
6155R-NPXP		X	X

VersaView 200R Specifications

(See <http://www.ab.com/versaview> for up to date specifications)

System Components	
Expansion Slots	1 PCMCIA slot (performance models)
Electrical	
Input Voltage, AC	90...264V AC, autoranging
Line Frequency	47...63 Hz
Power Consumption, AC	80 VA (0.18...0.07 A)
Environmental	
Operating Temperature	0...50°C (32...122°F)
Storage Temperature	-20...60°C (-4...140°F)
Humidity	10...90% without condensation
Vibration – Operating	0.006 in p-p, 10...57Hz; 1.0 g peak, 57...500 Hz sine
Vibration – Non-Operating	0.012 in. p-p, 10...57Hz; 2.0 g peak, 57...500 Hz sine
Shock – Operating	15g (1/2 sine, 11 ms)
Shock – Non-Operating	30g (1/2 sine, 11 ms)
Ratings	NEMA Type 1
Certifications	C-UL certified, UL recognized, CE marked, C-Tick
Mechanical	
Weight	2.1 kg (4.7 lb)
Dimensions Overall (H x W x D)	115 x 172 x 152 mm 4.54 x 7.68 x 5.98 in

www.rockwellautomation.com

Corporate Headquarters

Rockwell Automation, 777 East Wisconsin Avenue, Suite 1400, Milwaukee, WI, 53202-5302 USA, Tel: (1) 414.212.5200, Fax: (1) 414.212.5201

Headquarters for Allen-Bradley Products, Rockwell Software Products and Global Manufacturing Solutions

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444

Europe/Middle East/Africa: Rockwell Automation SA/NV, Vorstlaan/Boulevard du Souverain 36, 1170 Brussels, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640

Asia Pacific: Rockwell Automation, 27/F Citicorp Centre, 18 Whitfield Road, Causeway Bay, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846

Headquarters for Dodge and Reliance Electric Products

Americas: Rockwell Automation, 6040 Ponders Court, Greenville, SC 29615-4617 USA, Tel: (1) 864.297.4800, Fax: (1) 864.281.2433

Europe/Middle East/Africa: Rockwell Automation, Brühlstraße 22, D-74834 Elztal-Dallau, Germany, Tel: (49) 6261 9410, Fax: (49) 6261 17741

Asia Pacific: Rockwell Automation, 55 Newton Road, #11-01/02 Revenue House, Singapore 307987, Tel: (65) 6356-9077, Fax: (65) 6356-9011

Publication 6155R-PP001D-EN-P—May 2004

Copyright © 2004 Rockwell Automation, Inc. All rights reserved. Printed in USA.